


Redi-Purge™ *Ultra-High Efficiency*

Low Pressure Centrifugal Chiller Purge Unit



Features & Benefits:

Model PRG-11/123-C3

- Cost less than comparable purge units
- Ultra-High efficiency
- Easily connects to existing purge lines
- Mounts to existing mounting brackets
- Microprocessor-based controller
- Extensive operational LOGS
- Advanced diagnostics
- Operates independent of chiller operating status
- Optional carbon collection canister
- When replacing a Trane™ Purifier® or EarthWise™ Unit use model 007-11-C3 or 007-123-C3



Purge Efficiency...

Expels only .59 lbs CFC per lb. air removed. With optional Carbon Canister only .0049 lbs CFC per lb. air removed...

ETL Listed 3104248

SPECIFICATIONS

COMPRESSOR.....1/3 hp
PURGE TEMPERATURE.....0° F
ELECTRICAL.....103-127 VAC 60 Hz / 99-121 VAC 50 Hz
FUSED CIRCUIT.....15 Amp
FAULT RELAY.....Form C contact rating 120 VAC / 10 Amp
OPERATING ENVIRONMENT.....40° F to 120° F
WEIGHT.....110 lbs (shipping weight 140 lbs)
DIMENSIONS.....20" H x 16 W x 25" L
REFRIGERANT.....R-134a
FILTER/DRIER.....Dual One Pass vapor inlet
PIPING CONNECTIONS.....Gas Inlet 5/8" O.D. / Liquid Outlet 1/2" O.D

Carbon Canister (optional)

CARBON CANISTER.....equivalent to 50lb recovery cylinder
WEIGHT.....65 lbs (shipping weight 75 lbs)