

**INSTALLATION BENEFITS:**

- Unit can be mounted at eye level for operation and servicing convenience.
- Drilling or welding to the condenser shell is not necessary to install.
- The refrigerant charge in the chiller does not have to be removed to install.
- **COST LESS TO INSTALL THAN COMPARABLE PURGE UNITS.**
- **Simple Hook-up.**

**SPECIFICATIONS**

<b>OPERATING EFFICIENCIES:</b> <ul style="list-style-type: none"> <li>• The <b>Redi-Purge</b> High Efficiency Purge:</li> <li>• With the <b>Redi-Purge</b> Canister (Optional)</li> <li>• With the <b>Cryoline</b> Canister (Optional)</li> </ul>	<ul style="list-style-type: none"> <li>• Expels only .59 lb of CFC per lb. of air removed</li> <li>• Expels only .0049 lb of CFC per lb. of air removed</li> <li>• Attains .00040 lb CFC per pound of air</li> </ul>
<ul style="list-style-type: none"> <li>• <b>ELECTRICAL REQUIREMENTS:</b></li> </ul>	<ul style="list-style-type: none"> <li>• 103-127 VAC                      99-121 VAC</li> <li>• 60Hz                                      50 Hz</li> <li>• 1-Phase                                      1-Phase</li> <li>• 15 Amp Fused Circuit              15 Amp Fused Circuit</li> </ul>
<ul style="list-style-type: none"> <li>• <b>FAULT RELAY Output Rating</b></li> </ul>	<ul style="list-style-type: none"> <li>• 120 VAC - 240VAC</li> </ul>
<ul style="list-style-type: none"> <li>• <b>OPERATING ENVIRONMENT</b></li> </ul>	<ul style="list-style-type: none"> <li>• 40 F TO 120 F</li> </ul>
<ul style="list-style-type: none"> <li>• <b>STORAGE ENVIRONMENT</b></li> </ul>	<ul style="list-style-type: none"> <li>• -20 F TO 140 F</li> </ul>
<ul style="list-style-type: none"> <li>• <b>DIMENSIONS</b></li> </ul>	<ul style="list-style-type: none"> <li>• 20" H --16" W -- 25" L</li> </ul>
<ul style="list-style-type: none"> <li>• <b>WEIGHT</b></li> </ul>	<ul style="list-style-type: none"> <li>• 110 lbs (shipping weight 140 lbs)</li> </ul>
<ul style="list-style-type: none"> <li>• <b>CONDENSER REFRIGERANT</b></li> </ul>	<ul style="list-style-type: none"> <li>• R-134a</li> </ul>
<ul style="list-style-type: none"> <li>• <b>FILTER/DRIER (OEM Provided)</b></li> </ul>	<ul style="list-style-type: none"> <li>• Dual streamline One Pass vapor inlet filter-drier</li> </ul>
<ul style="list-style-type: none"> <li>• <b>FILTER/DRIER (Optional)</b></li> </ul>	<ul style="list-style-type: none"> <li>• 84 square inch liquid line filter-drier</li> </ul>
<ul style="list-style-type: none"> <li>• <b>CONNECTIONS</b></li> </ul>	<ul style="list-style-type: none"> <li>• Vapor Inlet ½" OD—Liquid Return ¼" OD</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Purge-Purge Canister (optional)</b></li> </ul>	
<ul style="list-style-type: none"> <li>• <b>CARBON COLLECTION CANISTER</b></li> </ul>	<ul style="list-style-type: none"> <li>• Equivalent to 50 lb recovery cylinder</li> </ul>
<ul style="list-style-type: none"> <li>• <b>WEIGHT (Carbon Collection Canister)</b></li> </ul>	<ul style="list-style-type: none"> <li>• 65 lbs. (shipping weight 75 lbs.)</li> </ul>
<ul style="list-style-type: none"> <li>• <b>DIMENSIONS (Carbon Collection Canister)</b></li> </ul>	<ul style="list-style-type: none"> <li>• Height: 19 ½" -- Diameter: 11 ½"</li> </ul>